Enhancing Aviation Safety and Efficiency Through Advanced Weather Sensing and Forecasting

Tim Bonin

8 May 2025





This material* is based upon work supported by the Department of Commerce, Department of the Air Force, Department of the Air Force and Federal Aviation Administration under Air Force Contract No. FA8702-15-D-0001 or FA8702-25-D-B002. Any opinions, findings, conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the Department of Commerce, Department of the Air Force, Department of the Air Force and Federal Aviation Administration.

© 2025 Massachusetts Institute of Technology.


Delivered to the U.S. Government with Unlimited Rights, as defined in DFARS Part 252.227-7013 or 7014 (Feb 2014). Notwithstanding any copyright notice, U.S. Government rights in this work are defined by DFARS 252.227-7013 or DFARS 252.227-7014 as detailed above. Use of this work other than as specifically authorized by the U.S. Government may violate any copyrights that exist in this work.

*Except where marked "This material is based upon work supported by the Observations Program within NOAA/OAR Weather Program Office under Award No. NA23OAR4590397."



Motivation





- Weather is the primary disrupter to air traffic in the US
 - Significant implications for the safety and efficiency of the National Airspace System (NAS)
 - Weather is a significant driver of flight delays & cancelations
- Weather sensing and forecasting aids Air Traffic Control (ATC) with both tactical and strategic planning





Primary Weather Conditions Impactful to Aviation








Icing



Turbulence



Wind Shifts and Shear



Winter Precipitation



Low Ceiling and Visibility



Weather Products Needed to Aid in Decision Making

En-route

Composite reflectivity

- Flexible layers
- Echo tops
- Forecasted airspace permeability

Convection and Thunderstorms

- Icing hazard layers
- Supercooled large droplets (SLD) layers

- Turbulence hazard layers
 - Clear-air turbulence
 - Mountain wave
- Convective growth products & reflectivity
 - Convectively induced turbulence

Turbulence

- Microburst & gust front detections
- Wind shift forecasting
- Headwind/crosswind
 - Runway configuration
 - Wake vortex separation assurance
- Wind gust potential

 Precipitation type/intensity sensing and forecasting

Icing

- Snow
- Ice Pellets
- Freezing rain / drizzle
- Mixed
- Frost forecasting

- Forecasts of visual flight rules (VFR) or instrument flight rules (IFR) conditions
- Fog / stratus dissipation or burn off timing

Wind Shifts and Shear

Winter Precipitation

Low Ceiling and Visibility



Outline


Motivation



- Weather Sensing and Forecasting for Aviation
 - Airport Sensing and Forecasting
 - En-route Sensing and Forecasting
 - RF Issues
 - Summary




Generalized Weather Information Pipeline






Tactical Airport Weather Sensing (0-2 Hours) Integrated Terminal Weather System (ITWS)





Strategic Airport Weather Forecasting (2+ Hours) Airport Capacity Evaluation and Prediction Tool (ACEPT)




ACEPT predicts airport weather, recommended runway arrival direction, resulting airport capacity, and identifies demand imbalances 8 hours into future to support effective collaborative decision making



Terminal Airspace Weather Forecasting Terminal Capacity Evaluation & Prediction Tool (TCEPT)

- Terminal airspace bridges the gap between airport and en-route operations
- TCEPT predicts waypoint availability & capacity to guide planning in convective weather
 - Assess availability of departure/arrival routes
 - Complementary to ACEPT
- Weather depicted from radar mosaics and HRRR model output
 - Radar-based at short time horizons
 - HRRR-based at long time horizons (2+ hours)






En-route Weather Sensing and Forecasting The NextGen Weather Processor (NWP)

- NWP developed to provide a "Common weather picture"
 - Available to all stakeholders
 - No conflicting weather information from multiple sources
 - Synthesizes many weather products (e.g., weather radar, geostationary satellite, weather models, surface weather observations, etc.)
- Improved safety:
 - Accurate storm location, size, shape, height, intensity through advanced mosaicking
 - More timely weather hazard information (25 sec updates)
- Improved efficiency:
 - Anticipation of airspace capacity impacts
 - Prediction of route availability and flow constrained areas
 - Support development of precise traffic flow initiatives
 - Miles-in-Trail restrictions, Ground Delay Programs and Airspace Flow Programs




NWP Coverage





NWP Depiction of Hurricane Milton – 25 sec CompRefl






NWP Mitigates of Wind Farms in Legacy Systems



Courtesy of Tri Nguyen and Dave Keifer 10/3/2024




- Wind farms create clutter that is notoriously difficult to remove in weather radar measurements
- Able to identify and remove through use of geostationary satellite imagery
- Mitigates nonweather echoes compared to legacy systems




En-route Weather Sensing and Forecasting: The Need for *Synthetic* Weather Radar

FAA

Domestic Jet Routes




- Piloted aircraft need to avoid hazardous weather for safety reasons
- Air Traffic Controllers lack sufficient weather radar coverage in offshore areas of the National Airspace System
- Controllers are unable to provide timely and accurate weather information to pilots in these regions



MITLL Solution:
Offshore Precipitation Capability (OPC)

DoD



Location of X- (green), C- (blue) and S- (red) band radars¹


- Weather radar information is non-existent or not accessible in many high interest areas
- Other forms of weather information (e.g., satellite, numerical models) may be insufficient to support operations

MITLL Solution:

Global Synthetic Weather Radar (GSWR)




Using Machine Learning to Extend Weather Radar Coverage Model Training






Using Machine Learning to Extend Weather Radar Coverage Model Execution





Offshore Precipitation Capability (OPC)





1 August 2017 1400 – 1700 UTC every 5 minutes



Outline

- Motivation
- Weather Sensing and Forecasting for Aviation




- RF Issues
 - Weather Radar Radiofrequency Interference
 - Usage of Aviation Bands for Weather Information
- Summary




Weather Radar Radiofrequency Interference (RFI)

- RFI is a common problem for weather radars
 - NEXRAD (S-band) most frequent sources:
 - Airport Surveillance Radars (ASRs)
 - Cell towers (4G LTE and 5G in the 2496-2690 MHz band), with out-of-band emissions up to 2765 MHz (see NTIA Report 13-490)
 - TDWR (C-band) most frequency source is Unlicensed National Information Infrastructure (U-NII) sources
 - Difficult to filter out due to high duty cycle and white noise in Doppler spectrum domain
 - Half of all sites experience RFI from U-NIIs
 - Dynamic Frequency Selection (DFS) function is required in this band, but improper installation, use, and failure to detect TDWR is problematic
- RFI can largely be censored but not filtered
 - May miss detections (e.g., wind shear events)



NEXRAD Affected by Cell Tower RFI in November 2019





Potential to Greatly Increase Weather Observations with Novel Low-Cost System

- The Portable Aircraft Derived Weather Observation System (PADWOS) can obtain dense observations
 - Low-cost (~\$12K) requiring only 28 W
 - Interrogates aircraft within 60 nm range
 - Able to retrieve temperature, wind speed, and wind direction aircraft is experiencing from received data
 - Transmits at 1030 MHz, aircraft replies at 1090 MHz
 - Initial test network set up around New England and the Southeastern United States
- Numerous potential uses of these measurements
 - Improve accuracy of weather models
 - Inform ATC operators of real-time conditions
 - Leverageable to enable time-based separation*





Challenges of Deployment of PADWOS Network

- PADWOS transmits at 1030 MHz, within the 960-1164 MHz band allocated for aeronautical radionavigation service (ARNS)
 - Managed domestically by the FAA
- Definition from NTIA: "The ARNS is a radionavigation service intended for the benefit and the safe operation of aircraft. There are numerous types of aeronautical radionavigation systems primarily used to ensure safety of flight and to support precision approach and landing of aircraft."
- Initial PADWOS installations have operated under a 2-year authorization from the FAA*
 - Authorization has recently expired and have been unable to obtain extended / new licenses for continued operations
 - Contend that PADWOS does benefit the safe operation of aircraft through enhanced weather situational awareness directly, and improved weather forecasts indirectly




Summary

- Weather is a significant challenge to the safety and efficiency of flight
 - Plethora of weather conditions can affect operations at any stage of flight
- Transformational weather sensing and forecasting technologies and systems have been developed to improve the safety of flight
 - Continue to be enhanced to address emerging problems as density of operations increases
- Radiofrequency allocation and usage has posed increasing challenges for advanced weather sensing



Backup






NWP Mosaic Techniques


• Sliding Volume updates: Compute new radar volume with every new tilt (15-40 sec)






NWP Mosaic Techniques

- **Sliding Volume updates:** Compute new radar volume with every new tilt (15-40 sec)








NWP Mosaic Techniques

- Sliding Volume updates: Compute new radar volume with every new tilt (15-40 sec)
- <u>Time-align tilts</u>: Track storms; time-align tilts; compute per-radar volume products
- Respect radar scan strategy: Compute trends only from "like" volumes








NWP Mosaic Techniques

- Sliding Volume updates: Compute new radar volume with every new tilt (15-40 sec)
- <u>Time-align tilts</u>: Track storms; time-align tilts; compute per-radar volume products
- Respect radar scan strategy: Compute trends only from "like" volumes
- Make mosaics: Motion-compensate all volumes to common mosaic time






Hurricane Milton – 2.5 min Echo Tops





Storm Hazard Tags





In addition to Echo Tops Tags, NextGen Weather provides Storm Hazard Tags as selectable option

LTNG (from FAA contract Lightning feed)


HAIL (based on Nexrad Hail product)

CIRC (based on Nexrad Mesocyclone product)

← Alternative lightning display (Can obscure Precip in severe lightning)




Example Mosaics in a Rapid Growth Scenario – Frontal Forcing





Rapid Storm Growth Indicated through Detectors



Excellent storm tracking allows accurate diagnosis of Trends


Precip updates: 2.5 min Trend updates: 25 sec




Traffic Flow Impact Predictions








Initial product: 8-hr predictions Future system release: 12-hr predictions








NWS Turbulence w/ NextGen Weather








NextGen Weather integrates NWS Turbulence on the Aviation Weather Display

Shown here are NextGen Weather 0-2 hr Fronts and Storm Motion Vecs overlaid on NWS Turbulence map



NWS Icing w/ NextGen Weather








NextGen Weather integrates NWS lcing and provides Layer selection option (floor/ceiling) for:


- NWS Icing (shown here)
- NWS Turbulence
- NextGen Weather Composite Reflectivity

Red contour indicates regions of super-cooled large droplets, known to cause aircraft icing



An emerging Radio Frequency Interference (RFI) Threat






- TDWR is equipped with time-domain single-pulse RFI detector and filter
 - Performs well against RFI from pulsed radars
- At the time of TDWR development and initial deployment (1990s)
 5.6-5.65 GHz band was restricted to certain radar systems
- In 2003 unlicensed national information infrastructure (U-NII) devices were allowed into this band
 - Dynamic frequency selection (DFS) function to sense and avoid radar channel is required
- U-NII (wireless communication) RFI is difficult to filter out
 - High transmit duty cycle
 - White noise in Doppler spectrum domain

Despite DFS requirement U-NIIs became an RFI challenge for TDWRs



U-NII-to-TDWR RFI Timeline



experience RFI from U-NIIs



Why DFS "Sense and Avoid" is not Working as Intended*

- Willfully improper installation and operation of U-NIIs
 - Disabling DFS function—made more difficult by 2014 requirement of locked country codes
 - Connection to non-compliant high-gain antennas
 - Illicit retuning of non-DFS-equipped wireless devices into TDWR band
 - Illegal import of non-US-authorized devices
- Failure of certified DFS to detect TDWR
 - Original test did not include waveforms representative of TDWR; there may be other issues
 - Waveform set and procedure revised in 2014; but TDWR has new waveforms since then
- Post-certification firmware updates unintentionally disabling DFS function
- Only the master device in U-NII local network is required to have DFS
 - If master device is more blocked from radar view than clients, DFS may not detect radar and clients transmissions could cause interference to radar
 - Not documented so far, but physically possible


Problem cannot be solved by technical approach alone



Mitigation Approaches

- Regulatory enforcement: Track down offenders, levy fines, shut them down
 - Like game of "Whack-a-mole": New and repeat offenders keep popping up
- Technical measures
 - Dynamic "noise" floor estimation and subtraction: Effective if INR not big relative to weather SNR
 - Automated detection and censoring
 - · Would help avoid false alerts on wind-shear detection
 - Would not help with missed detections due to obscuration by RFI*
- Institute exclusion zones around TDWRs?
 - Could affect significant fraction of U.S. population
 - Illicit operation still a problem

TIGER TEAM




U-NII RFI is an ongoing issue

^{*}No documented case of missed detection or false alert due to RFI yet



Portable Aircraft Derived Weather Observation System (PADWOS)

Range	60 NM (per agreement with FAA)
Observation Period	e.g., 10 - 60 s (programmable)
Observation Delay	<< 1 s
Network Connectivity	4G
Power Requirement	~ 28 Watts
Prototype Cost	< \$US 12k













Comparing Current System





PADWOS Single Day, Single Site Comparison to MDCRS



Accuracy of estimates from PADWOS are on par with current MDCRS measurements