When [...] we hear the loud boom of a waterfall, we know that the stream is descending a precipice. If a heavy rumble and roar, then we know it is passing over a craggy incline. [...] The young river speaks and sings all the smaller characters of the smooth slope and downy hush of meadow as faithfully as it sings the great precipices and rapid inclines, so that anyone who has learned the language of running water will see its character in the dark. - John Muir (Mountain Thoughts) The Language of Water New insights into river processes from seismic signals

Danica Roth

Colorado School of Mines


Seismic data is providing new insights on urgent issues in environmental and Earth surface processes



slow/continuous Timescales fast/impulsive

Environmental seismology offers unique advantages and opportunities for research across many fields


- Process monitoring and event detection
- Characterization of near surface materials and properties
- Links to energy transfer and budgets
- Insights into process coupling and cascades




New fluvial insights from seismology


Glacial lake outburst floods, rather than precipitation, mobilize channel-stabilizing boulders and may drive long-term fluvial erosion in the Himalaya.

Seismic records reveal seasonal transitions in sediment supply driven by typhoon-induced landslides in Taiwan.




Low frequency horizontal ground motion (tilt) may reveal surface deformation due to precipitation loading, or fluctuating pressure on streambanks linked to turbulent eddy dynamics.







Cook et al, 2018 Chao et al, 2015

Yang et al, 2018









Process rates are recoverable from seismic spectra... with enough independent constraints

Least squares regression of PSD at each frequency identifies the spectral contributions from each process




Process rates are recoverable from seismic spectra... with enough independent constraints

Least squares regression of PSD at each frequency identifies the spectral contributions from each process



Measured discharge, precipitation and PSD can then be inverted to predict transport



flood 1


transport

NO transport

Roth et al, 2014


Roth et al, 2014






Roth et al, 2014





Hysteresis in both sediment transport rates and seismic signals are commonly observed over discrete flood events. Schmandt et al., 2008; Hsu et al., 2011; Schmandt et al., 2013; Roth et al., 2014; Díaz et al., 2014; Chao et al., 2015





Roth et al, 2014


Seismic hysteresis tracks sediment transport patterns after dam removal

Hysteresis at each seismic station over subsequent floods shows downstream advection and dispersion of a sediment pulse released from behind the dam.










Hysteresis in seismic signals and sediment transport rates do not match

Roth et al, 2017

Seismic power is higher when transport is lower for 4 out of 5 flood events!

Sediment transport hysteresis



Seismic sensitivity to water turbulence both a major challenge and an opportunity

The bed surface fundamentally controls water turbulence—hysteresis due to changes in sediment flux versus the turbulent boundary layer cannot be distinguished without additional data

Can seismic signals provide new information on turbulent flow dynamics and bed organization?

Discharge

Theoretical model advances are closing the gap between seismic observations, flow characteristics and sediment transport theory


Several models developed for theoretical bedload and water turbulence spectra (Tsai et al, 2012; Gimbert et al, 2014, 2016)

Inversion of observed spectra to estimate transport requires site-specific parameters and is complicated by overlap of spectra

Recent computational advances are providing new tools for optimizing parameters
(Dietze et al, 2018)

Model validation remains a major challenge, requires more controlled studies with well-constrained parameters and variables

(e.g., Gimbert et al, 2019)



Dietze et al. 2019

Power (dB)

Bedload flux

Synthetic PSD 4

Deviation matrix 4


Time series 4

08:00 Time(UTC)


Error model 4




Polarity reversals created by "tap tests" identify DAS channels at key positions









Polarity reversals created by "tap tests" identify DAS channels at key positions








Isolated water turbulence signal




Isolated water turbulence signal

Frequency shifts due to changing flow depth or channel width?

May explain similar observations in less well-constrained data, e.g., after dam removal:








Opportunities

- Continuous record of existing data in many places
- Identification of rare events, forcing/precursors and process cascades
- High spatial/temporal resolution for process monitoring (large arrays, DAS)
 - With independent calibration/data: direct estimates of sediment transport rates
 - Without independent calibration/data: tracking of qualitative patterns, relative rates
- Characterizing bed organization/evolution or energy transfer

Challenges/Needs

- Complex coupling between sediment transport, hydraulic parameters and environmental variables
- Site-specific attenuation (i.e., empirical Green's functions) riverbeds are heterogeneous!
- Parallel development and validation of theoretical models will require controlled seismic deployments co-located with traditional instrumentation to independently measure environmental variables
 - Weather/meteorological data
 - Water level/discharge
 - Sediment transport rates

- High resolution topography/change detection
- Substrate characteristics (attenuation)
- Video/time-lapse imagery





Acknowledgements

Funding and support provided by:
NSF Geomorphology & Land Use Dynamics,
Incorporated Research Institutions for Seismology (IRIS)
PASSCAL Instrument Center, Eugene Cota-Robles
Fellowship, DOE National Nuclear Security
Administration, CSM Geophysics Department, CSM
Dean's EREP and CSM VPRTT

Collaborators/Coauthors:

Noah Finnegan, Emily Brodsky, Jens Turowski, Dieter Rickenmann, Alexandre Badoux, Florent Gimbert, Claire Masteller, Jin Ge, Aleksei Titov, Matt Siegfried, Luke Zoet

— Supplemental ————



Erlenbach, Switzerland

Fast and easy deployment near expected event sites





Arattano and Moia, 1999


seismic stations

recording equipment











Calving event from Yahtse Glacier





Microseisms

Oceanic and atmospheric phenomena



Hurricane physics observed with seismics & pressure sensors





Nuuggaatsiaq landslide, Greenland June 17, 2017

> Short-period (>1 Hz) Long period (<0.05 Hz)

> > Detectable


volume (m³)

Undetectable

max distance (km)

10


10⁰



Lahar on Volcán de Colima

frequency content changes as different parts of the flow pass by the station (located about 100m from the channel)






25 June 2012


(from Vázquez et al., (2016)


Seasonal glaciohydraulic tremor interpreted as subglacial flow

Yahtse Glacier, AK





Frequency Spectrum Analysis







shifting frequencies during flooding events have been observed in other studies and attributed to decreases in velocity as sediment becomes water saturated (Anthony et al, 2018)











Does not fit 1.6km/s

F-K analysis for velocity





-0.3

-0.2

-0.1

0.0

Wave Number (1/m)

0.1

0.2

0.3

Why do rivers matter?















Seismic records provide new insights into glacial lake outburst flood mechanics

Cook et al, 2018


Mobilization of channel-stabilizing boulders by glacial lake outburst floods—rather than precipitation—may drive long-term fluvial erosion and valley evolution downstream of glaciers in the Himalaya.

Low frequency horizontal ground motion (tilt) may reveal turbulent eddy dynamics or precipitation loading

0.1–2 Hz H/V acceleration power interpreted as hyporheic zone deformation by fluctuating pressure on streambanks by large-scale turbulent eddies.



Low frequency horizontal seismics could enable continuous monitoring of average discharge and large eddy dynamics, estimates of average water loading over ≤ 10s of kilometers, constrain decadal rainfall records,



< 0.3 mHz velocities correlate with rainfall and rate of change in river flow depth.

Measuring and predicting fluvial sediment transport is a fundamental need—but extremely challenging

Fluvial sediment transport models rely on empirical calibration




Laboratory experiments




Photos: Jim O'Connor, USGS




Permanent instrumentation




Regression for a_f , b_f , c_f at each frequency identifies the relative spectral contribution of each process





Roth et al (2016), Regression coefficients represent normalized power spectra at each seismometer

(seismic power per unit p, Q or q_s)



Broadband

signal dominated by rainfall directly above seismometers


Higher frequencies attenuated

dominant signal source is more distant

Turbulence and transport spectra overlap

Process rates are recoverable from seismic spectra... with enough independent constraints


Least squares regression of PSD at each frequency identifies the spectral contributions from each process



Spectral peaks are strongly moderated by attenuation— site-specific parameters and distance from channel matter!




Changing flow velocity by >10% accounts for hysteresis



Calculated from Gimbert et al. (2014)






Rougher beds generate less turbulence due to form drag

e.g. Lamb et al., 2008

Calculated from Gimbert et al. (2014)



Changing bed roughness by >30% accounts for hysteresis



Calculated from Gimbert et al. (2014)



Rearrangement of grains likely causes hysteresis in both sediment transport and water turbulence

Reversal of Ψ_S and Ψ_G cannot be explained by any process that causes positively correlated hysteresis in turbulence and sediment transport

Semi-stochastic changes in shear velocity and bed roughness due to:

- Erosion/aggradation of the bed around large boulders
- Shifting of boulders






Rearrangement of grains likely causes hysteresis in both sediment transport and water turbulence

Channel hydraulics (e.g., flow depth and velocity) on the Erlenbach are highly sensitive to the degree of boulder protrusion above the bed.



Yager et al., 2007


The bed surface fundamentally influences water turbulence



Does seismic hysteresis reflect changes in the sediment flux, or in the turbulent boundary layer?

Discharge

Seismic sensitivity to water turbulence is both a major challenge and an opportunity




~10% change in flow velocity or ~30% change in bed roughness could account for observed hysteresis in seismic power



Bed reorganization around boulders may cause semi-stochastic changes in shear velocity and bed roughness

Roth et al, 2017

Seismic sensitivity to water turbulence is both a major challenge and an opportunity



Can seismic signals provide new information on turbulent flow dynamics and bed organization?



Bed reorganization around boulders may cause semi-stochastic changes in shear velocity and bed roughness

Roth et al, 2017

