

Presentation to Astro 2020 NAS Decadal Committee

Ms. Kendra Short, Exoplanet Exploration Program Deputy Manager, JPL

Dr. Phil Willems, Starshade Technology Manager, JPL

Jet Propulsion Laboratory

California Institute of Technology

November 19, 2019



Contributors























University of Colorado Boulder




2010 Decadal Called for Technology Investment


Decadal Survey Recommendation:

"Candidate starlight suppression techniques be developed to a level such that mission definition for a space-based planet imaging and spectroscopy mission could start late in the decade."

APD Response:

- Strategic Astrophysics Technology (SAT)
 - Competitively selected individual investigator awards to address mid-TRL technologies (3-5)
- In 2016, the starshade was spun off to establish a starshade technology development activity with the goal of advancing starshade technology to TRL 5





Programmatic Context



NASA Charters Starshade Technology Activity (March 2016)

Technology Activity Goals:

- "to mature the required techniques to the point at which starshades could be integrated into potential future exoplanet detection and characterization missions"
- Advance critical capabilities to TRL 5 and close key technology gaps*:
 - Starlight suppression
 - Formation flying
 - Deployment of large-scale, precision structures



^{*} reference ExEP Technology Plan Appendix



Reference Mission Concepts for Starshade Technology

Habitable Exoplanet Observatory



Telescope Diameter: Starshade Diameter: Separation:

IWA:

4 m 52 m 76,600 km 70 mas

WFIRST-Rendezvous Probe



Telescope Diameter: Starshade Diameter: Separation:

IWA:

2.4 m 26 m 26,000 km 103 mas



Starshade Technology Gaps



Suppressing diffracted light from onaxis starlight and optical modeling




Suppressing scatted light off petal edges from off-axis Sunlight

(2) Formation Sensing

Sensing the lateral offset between the spacecraft







(3) Shape Accuracy and Shape Stability

Fabricating and positioning the petals to high accuracy Maintaining shape stability over operational conditions





What is Technology Readiness Level 5?

Definition

Component and/or breadboard validation in relevant environment.

Per NPR 7123.1B Appendix E

TRL 5

Exit Criteria

Documented test performance demonstrating agreement with analytical predictions.

Documented definition of scaling requirements.

Per NPR 7123.1B Appendix E

Hardware Description

Performance/Function

Demonstrate overall performance in critical areas

Fidelity of Build

Medium fidelity system/component brassboard with realistic support elements

Supporting Analysis

Performance predictions are made for subsequent development phases

Environment Verification

Simulated relevant operational environment.

From "JPL Technology Readiness Assessment Guideline" 2016





S5 Error Budget Defines Key Performance






Balanced Use of Scale and Fidelity









S5 Simulation and Model Validation is Critical

Everything flows from optical performance models


There won't ever be a full-scale system test of a starshade at flight conditions


Confidence in our models and requirements through sub-scale testing and validation


Independent analysis and modeling where possible


Diverse collection of analytical tools:


- Optical Model and error analysis tool
- SISTER optical simulation tool
- Formation control simulation
- Mechanical finite element model
- Thermal model
- Dynamic deployment models
- Stray light /scattered sunlight models






















Technology Development Plan and Milestones

arshade to TRL5 (SS) Technology Development Plan



Starshade to TRL5 (S5) Technology Development Plan

September 13, 2018

Document Owner: Phil Willems S5 Technology Development Deputy Manager Jet Propulsion Laboratory California Institute of Technology

National Aeronautics and Space Administration

Jet Propulsion Laboratory California Institute of Technology Pasadena, California

https://exoplanets.nasa.gov/exep/technology/starshade/

MS	Demonstration	KPP
1A 1B 2	Optical Contrast – Narrowband Optical Contrast – Broadband Optical Validation - MUF	10 ⁻¹⁰ 10 ⁻¹⁰ 1.25
3	Scattered Sunlight	Vis Mag > 5
4	Lateral Sensing	± 30 cm
5A 6A 7A 7C 8A	Petal Shape Accuracy – Crit Features Petal Shape Stability – Crit Features Truss Bay Accuracy – Crit Features Inner Disk Accuracy – Crit Features Truss Bay Stability – Crit Features	± 70 μm ± 80 μm ± 300 μm ± 300 μm ± 200 μm
5B 6B 7B 7D 8B	Petal Shape Accuracy – All Features Petal Shape Stability – All Features Truss Bay Accuracy – All Features Inner Disk Accuracy – All Features Truss Bay Stability – All Features	± 70 μm ± 80 μm ± 300 μm ± 300 μm ± 200 μm

Independent review and approval of milestone definition and completion by ExEP's Technology Assessment Committee (ExoTAC)



Public Dissemination of S5 Results



to be to "...manage exoplanet-related technology initiatives, including the management of specifically directed technology activities, facilitation of a coordinated NASA Astrophysics technology identification/prioritization process, oversight of competitively-selected technology activities, and certification of technology milestones and or Technology Readiness Levels (TRLs) *1

A key method in the pursuit of these goals and objectives is the direct imaging of planets around other stars. Directly sampling the light from an exoplanet separately from that of its host star facilitates measurement of its size, orbit, albedo, and ground and atmospheric spectra, which provide clues to its habitability, and potentially could provide signatures of the presence of life itself. However, direct observation of small, rocky planets like Earth close enough to their host stars to harbor liquid water is very difficult due to the extreme faintness of the exoplanet relative to the very nearby star. The starlight must be suppressed, either interferometrically or by an occulter to allow exonlanet detection. Occulters that are internal to the telescope are referred to as coronagraphs. Occulters that are external to the telescope are referred to as starshades

Starshades benefit NASA by enabling and enhancing NASA's capability to detect planets around other stars, characterize them, and search them for signs of life. They do this by dramatically extending the 'field of regard' of direct imaging studies towards small, rocky planets orbiting in the habitable zones of their host stars, the regions where liquid water can be sustained on the planets' surfaces, and towards characterization of the surfaces and

In 2016, NASA's Astrophysics Division Director approved a proposal by the ExEP to restructure its starshade-related technology development investments into a focused activity to bring starshade technology to Technical Readiness Level 5 (TRL5).2 This focused activity is called S5. In September 2018, NASA's Astrophysics Division approved the plan to proceed with the implementation of S5 to address the three most critical technologies for Starshades. These technologies are: starlight suppression, formation sensing and control, and deployment accuracy and shape stability.

Videos



10m Starshade Inner Disk Deployment

This video shows the deployment of the 10m Inner Disk Subsystem prototype hardware in the test facility at Tendeg



Starshade Rendezvous Mission Concept Animation

This animation depicts the on orbit separation and deployment of a Starshade System and Telescope System that were co-launched. This represents a potential mission



Starshade Wrapped Architecture Deployment Concept

This animation shows the transition of the starshade from the stowed configuration to the deployed configuration including the eventually jettison of the Petal Launch and Unfurl Subsystem (PLUS).



Lateral Sensing Simulation

This video shows a simulation of the translation of the out-of band starlight (Arago spot) in the telescope camera used for lateral sensing and formation flying maneuvers.

- . Starshade Technology Development Plan
- Level 1 Technology Milestones -

Milestone #1

- . 1A Report Narrowband Optical Contrast
- . 1B Report Broadband Optical Contrast
- . ExoTAC Review of #1A #1B

- . Report Formation Flying
- ExoTAC Review

External Links

- · Starshade Imaging Simulation Toolkit for Exoplanet Reconnaissance (SISTER)
- Starshade Rendezvous Mission (SRM) -Probe Study Report

Starshade Science and Industry Partnership (SIP)

SIP Documents

- Terms of Reference (5/30/2019)
- Technology and Science Working Group
- SIP TSWG Members
- . Small Business Awards Notice

SIP Meetings and Presentations

Upcoming SIP Face to Face Meetina

Date: February 6-7, 2020

Please save the date for the second Starshade SIP forum on February 6-7, to be held in Boulder, Colorado.

SIP Mailing List

To subscribe to the SIP mailing list, send an

S5 Starshade Technology web-page

https://exoplanets.nasa.gov/exep/technology/starshade/

- Important Resources:
 - S5 Technology Development Plan
 - Milestone Reports and ExoTAC Reviews
 - Starshade Technology Status Reports
 - SIP Forum Presentations (webex and F2F)
 - Links to relevant publications and webpages
 - Starshade graphics, videos and other materials
- Milestone results also published in technical journals and presented at conferences.



S5 Technology Milestones Scorecard

Complete March 2020



Complete June 2023

Starlight Suppression







Contrast NB 1A


Modeling 2

Scattered Sunlight



1B

Edges 3





Sensing 1

Critical Features

Shape Accuracy







Petal 5A

Truss Bay 7A

Inner Disk 7C

Shape Stability





Inner Disk 8A



All Features







Petal 5B

Truss Bay 7B


Inner Disk 7D



 \bigcirc

Petal 6B


Inner Disk 8B





Narrowband Contrast Demonstration


Small scale starshade mask in the Princeton Testbed demonstrates 1×10^{-10} instrument contrast at the inner working angle in narrow band visible light and Fresnel number ≤ 15 .



REQUIREMENT MET:

Achieved < 10⁻¹⁰ contrast at 44% of IWA, best performance to date of a starshade at a flight-like Fresnel number.

Limits to contrast at small scale are well understood.




STATUS: Complete



Broadband Contrast Demonstration

Small-scale starshade mask in the Princeton Testbed demonstrates 1 × 10⁻¹⁰ instrument contrast at the inner working angle at *multiple wavelengths* spanning ≥ 10% bandpass and Fresnel number ≤ 15 at the longest wavelength.



REQUIREMENT MET:

Achieved < 10⁻¹⁰ contrast at IWA, for all wavelengths tested.

STATUS: Complete



Optical Contrast Model Correlation

Small-scale starshade masks in the Princeton Testbed validate contrast vs. shape model to within 25% accuracy for induced contrast between 10⁻⁹ and 10⁻⁸.


KPP 2

APPROACH:

Test deliberately misshapen masks to verify that contrast varies with shape error as predicted.

STATUS:

Contrast varies with shape as expected in masks tested to date.




STATUS: In process, complete 3/20


Solar Glint

Optical edge segments demonstrate scatter performance consistent with solar glint lobes fainter than visual magnitude 25 after relevant thermal and deploy cycles. $_{\rm KPP\,3}$

RESULTS:

- System model shows scatter lobe dimmer than V = 25 mag for all wavelengths and nearly all sun angles.
- No degradation in scatter performance after exposure to environments.






STATUS: In review




Formation Flying

Starshade Lateral Alignment Testbed validates the sensor model by demonstrating lateral position offset sensitivity to a flight equivalent of 30 cm. Control system simulation using validated sensor model demonstrates onorbit lateral position control to within ± 1 m.



REQUIREMENT MET:


- Starshade lateral offset measured to 10 cm flight equivalent.
- Formation flying simulation controlled position to $\pm\,1$ m.
- Large margins on stellar magnitude, allowable measurement error.



STATUS: Complete, formation flying at TRL 5



Starshade Structural Subsystems



11/19/2019 2⁻



Stowing and Deployment




Stowing the inner disk






Stowing the petals







Starshade Structural Subsystems



11/19/2019 23




Starshade Shape Accuracy - Petal

Petal subsystem demonstrates total prelaunch shape stability (manufacture, deploy cycles, thermal cycles deployed, and storage) consistent with a total pre-launch shape accuracy within \pm 70 μ m.

RESULTS:

Shape-critical element prototype meets requirement after stow-and-deploy and thermal cycles.







First article 12/2019, TRL 5 by 6/2023



Starshade Shape Accuracy - Inner Disk

Truss Bay assembly demonstrates dimensional stability with thermal cycles (deployed) and storage consistent with a total pre-launch petal position accuracy within \pm 300 µm.


Inner Disk Subsystem with optical shield assembly demonstrates repeatable accuracy consistent with a total prelaunch petal position accuracy within


 \pm 300 μ m.


KPP 7


RESULTS:

Shape-critical element prototype meets requirement after stow-and-deploy and thermal cycles.










First articles 12/2019, TRL 5 by 6/2023



Starshade Shape Stability - Petal

Petal subsystem demonstrates on-orbit length thermal stability within $\pm 80~\mu m$ by analysis using a validated model of critical dimension vs. temperature. KPP 6



First article 12/2019, TRL 5 by 6/2023



Starshade Shape Stability - Inner Disk


Truss Bay assembly demonstrates on-orbit thermal stability within \pm 200 μ m by analysis using a validated model of critical dimension vs. temperature.

APPROACH:

- Initial tests validate on-orbit finite element models of longeron and node subassemblies
- Final TRL 5 test validates model at truss bay assembly level.

RESULTS:

Longerons and nodes meeting requirements with margin.





First articles 12/2019, TRL 5 by 6/2023

11/19/2019 2




Fechnology Development Plan and Milestones

MS	Demonstration	KPP	Date
1A 1B 2	Optical Contrast – Narrowband Optical Contrast – Broadband Optical Validation – MUF	10 ⁻¹⁰ 10 ⁻¹⁰ 1.25	Jan 2019
3	Scattered Sunlight	Vis Mag > 25	Nov 2019
4	Lateral Sensing	± 30 cm	Nov 2018
5A 6A 7A 7C 8A	Petal Shape Accuracy – Crit Features Petal Shape Stability – Crit Features Truss Bay Accuracy – Crit Features Inner Disk Accuracy – Crit Features Truss Bay Stability – Crit Features	± 70 μm ± 80 μm ± 300 μm ± 300 μm ± 200 μm	Dec 2019 Dec 2019 Dec 2019 Dec 2019 Dec 2019 Dec 2019
5B 6B 7B 7D 8B	Petal Shape Accuracy – All Features Petal Shape Stability – All Features Truss Bay Accuracy – All Features Inner Disk Accuracy – All Features Truss Bay Stability – All Features	± 70 μm ± 80 μm ± 300 μm ± 300 μm ± 200 μm	Jun 2023



Summary



S5 is successfully developing the enabling technologies for HabEx and Starshade Rendezvous.





This work was conducted at the Jet Propulsion Laboratory, California Institute of Technology, under contract with the National Aeronautics and Space Administration.

© 2019 California Institute of Technology. Government sponsorship acknowledged.