


Emerging Technologies for Mars Exploration

Chad Edwards

Jet Propulsion Laboratory, California Institute of Technology chad.edwards@jpl.nasa.gov

Jan 5, 2021



Agenda

- Introduction
- Selected Technology Areas
 - Enabling technologies for Mars Sample Return
 - Enhanced surface mobility
 - Access to the subsurface
 - Small spacecraft capabilities
- Summary

Introduction

- Mars exploration capabilities have progressed dramatically over more than two decades of continuous robotic presence at Mars
 - Orbital
 - High-bandwidth remote sensing
 - Landing site reconnaissance
 - Telecommunications relay infrastructure
 - Surface
 - Increased landed mass
 - Increased mobility
 - Improved landing accuracy
 - Enhanced sampling capabilities
- Addressing the next layer of Mars science questions will demand new exploration capabilities and associated technology investments over the coming decade



Emerging Capabilities for Mars Exploration

C. D. Edwards, Jr. M. J. Amato², J. D. Baker¹, N. J. Barba¹, J. Balaram¹, E. J. Brandon¹, P. Briggs¹, B. D. Davis³, J. C. Day¹, A. Freeman¹, M.R. Grover¹, G. S. Hubbard⁴, D. B. Lavery⁵, L. Mandrake¹, L. H. Matthies¹, G. Meirion-Griffith¹, M. M. Munk⁶, I. A. Nesnas¹, R. W. Obbard⁷, M. Ono¹, M. A. Peck⁸, V. Stamenković¹, S. A. Townes¹, T. G. Trenkle², E. Venkatapathy⁹, K. A. Zacny¹⁰

¹Jet Propulsion Laboratory, California Institute of Technology, ²NASA GSFC, ³NASA MSFC, ⁴Stanford University, ⁵NASA Headquarters, ⁶NASA LaRC, ⁷SETI Institute, ⁶The Johns Hopkins University Applied Physics Laboratory, 9NASA ARC, 10Honeybee Robotics


Contact: C. D. Edwards, Jr. (Jet Propulsion Laboratory, California Institute of Technology) email: chad-edwards@jpl.nasa.gov, phone: 818.354.4408



Artist concept of the Ingenuity Helicopter demo on Mars 2020



Tethered Rover



mission concept



and energy-aware path planning






© 2020. All rights reserved.

Enabling Technologies for Mars Sample Return


Mars Ascent Vehicle

Baseline Design



- Launch Orbiting Sample (OS) into 380 km circular orbit
- Two-stage (guided, unguided) solid motor vehicle
 - 1st-stage electromechanical Thrust Vector Control
 - 2nd-stage spin/de-spin motors
 - Monoprop Reaction Control System
- MAV Payload Assembly (MPA)
 - Ejectable fairing
 - Orbiting Sample (OS)


Planetary Protection/Containment Assurance



- Capture, Containment and Return System (CCRS) Concept
 - Capture and Containment Module
 - Capture OS in Mars orbit, constrain & orient
 - Break-the-Chain and Containment Assurance
 - Transfer contained OS to Earth Entry Vehicle
 - Earth Return Module
 - MMOD protection
 - Earth Entry Vehicle for robust delivery to landing site

Access to New Regions on Mars

- Mars in situ missions to date have been limited to surface and near-surface (<10 cm) access in regions compatible with current lander/rover capabilities
- Next phases of Mars exploration can be enabled by capabilities for accessing new regions
 - Extended mobility
 - Accessing diverse geologic environments
 - Extreme terrains
 - Gullies and RSLs
 - Exposed scarps
 - Polar Layered Deposits
 - Subsurface
 - Sounding for subsurface groundwater
 - Drilling to depths relevant for determining modern-day subsurface habitability



Exposed Ice Scarps



Deep Subsurface TEM

Pre-Decisional Information – For Planning and Discussion Full Decision & Drilling Concepts



Polar Layered Deposits



Recurring Slope Lineae

Extended Mobility - Long-Range Rovers

- MEPAG and MASWG both advocate exploring the diversity of Mars surface environments
- Options
 - Multi-rovers high cost of multiple vehicles and EDL systems
 - Long-range rover need to achieve drive distance capabilities of 100-1000 km to span distinct geologic units
- Prior capabilities:

	Total Drive (km)	Duration (yr)	Avg Rate (km/yr)	Max Drive Sol (m)
Spirit	7.7	6.2	1.2	124
Opportunity	45	14	3.2	220
Curiosity	24.1	8.4	2.9	142



Bulk metallic glass gears in planetary gearboxes

Aeolis Planum
(MFF)

Aeolis Planum
(MFF)

Royal And Amazonian Lavas


Aeolis Planum
(MFF)

Royal And Amazonian Lavas

Noachian Highlands


Medusae Fossae Formation traverse example (825 km)





Deep learning-based terrain classification

- Long-range mobility target: >1 km/sol drive capability
 - Could achieve >350 km/Mars year, assuming 50% drive sols
- Key technology needs for achieving long-range mobility:
 - Heaterless, high-speed mobility actuators (30 cm/sec drive speed) employing bulk metallic glass gears
 - Onboard autonomy enabling map-based position estimation, terrain classification, and rapid recovery from driving faults
 - High-performance, low-SWaP avionics



Rover Map-based position estimation



Long-range autonomous drive demo in JPL Arroyo

Axel Rover Concept

- Tethered mobility system enables access to slopes >>25 deg
- >100m rappel distance
- Instrument bays in each wheel can accommodate multiple instrument payloads
- Key technical challenges:
 - Robust tether management
 - Instrument accommodation and deployment
 - Autonomous tethered navigation in complex slope environments








Issa Nesnas/JPL




Mars Rotorcraft Concept


- Mars rotorcraft offer a compelling new platform for in situ exploration
 - Mesoscale access
 - Greater range than rovers
 - Better resolution than orbiters
 - Extreme terrain access
 - Slopes, gullies, scarps, ...
 - Atmospheric boundary layer access
- Key challenges
 - Extremely low Mars atmospheric density
 - Autonomous flight navigation and landing



Ingenuity Mars Helicopter Technology Demonstration

- Solar powered up to one 90-second flight per day
- Flight Range up to 300 m
- Heights up to 10 m
- Autonomous flight & landing
- Blade design for thin atmosphere
- Able to survive cold Martian nights








Pre-Decisional Information – For Planning and Discussion Purposes Only

Mars Science Helicopter Concept

 JPL & ARC are currently studying how to move beyond MHTD to a fully capable Mars Science Helicopter platform

- Reference Design
 - Up to 30 kg system mass
 - Hexacopter configuration (also studying co-axial option)
 - Advanced navigation capabilities
 - Autonomous Landing Site Detection
 - All-Terrain Navigation
 - Long-range Map-based Navigation
 - Assessing mid-air delivery system for low-cost mission concepts not requiring a base lander
 - Key technology needs:
 - Aerodynamic design & modeling
 - High specific power & energy batteries
 - Low-SWaP avionics and instruments








Field testing of Earth-based demonstrator UAV

Subsurface Access


- The Martian subsurface is a prime target for astrobiology
 - Shielded from surface radiation environment
 - Potential for liquid water aquifers
 - Potential modern habitable environment and abode for extant life


See the PSADS White Paper "Deep Trek: Science of Subsurface Habitability & Life on Mars - A Window into Subsurface Life in the Solar System", V. Stamenkovic, K. Lynch, P. Boston, J. Tarnas, et al.)





Remote Sensing – Transient Electromagnetic Sounding

- Transient Electro-Magnetic (TEM) sounding provides capability of detecting and characterizing Martian groundwater
 - TH₂OR (<u>Transmissive H₂O Reconnaissance</u>) instrument concept in development at JPL











Deep Drilling

- Wireline drill concept for accessing depths of 10s-100s m with low mass and power
- Leverage demonstrated, highly reliable, terrestrial rotary-percussive drill technology, with key innovations for use on Mars:
 - Reduced drill bit diameter (3 cm)
 - Reduced mass and power (<100 kg, <100 W)
 - Autonomous operations
 - Use of compressed liquid CO₂ (extracted from Mars atmosphere) to power drill
 - Same CO₂ upon vaporizing serves to flush cuttings from borehole into bailing bucket
 - Sub-mm fused silica capillary serves as wireline and also as conduit for pressurized CO₂
 - All downhole parts rated for > 350°C, enabling straightforward sterilization
- Instrument options
 - Borehole fiber for UV/Raman spectroscopy
 - Sample delivery to lander deck for TLS for isotopologue analysis, or more sophisticated organics analyzers (e.g., MOMA, SAM)









Honeybee Wireline Drill Prototypes

Courtesy: K. Zacny


Low-Cost Access to Mars

- Small Mars spacecraft missions can achieve compelling science at a fraction of Discovery costs
 - Leverage emerging commercial
 Cubesat/Smallsat spacecraft subsystems
 - Formulate science mission concepts with focused instrument payload suite
 - Utilize low-cost methods to deliver small spacecraft to Mars
 - Piggyback on Mars-bound mission primary mission
 - Rideshare to GTO or Earth escape
 - Launch on new class of small low-cost LVs (e.g., Firefly, Relativity)
 - Mars small spacecraft missions can be further enabled by improved relay capabilities to support both landed and orbiting small spacecraft




AREO TGL: High Orbit Concept Case Study

Areostationary Trace Gas Localizer



Surface/Subsurface Concept Case Study

SHIELD Impact Lander Concept





Summary

- New capabilities are needed to enable the next era of Mars exploration
- Examples presented here:
 - Key MSR technologies
 - Mars Ascent Vehicle
 - Back Planetary Protection/Containment Assurance
 - Enhanced surface access
 - Rotorcraft
 - Tethered rovers
 - Long-range rovers
 - Access to the Martian subsurface
 - TEM remote sensing
 - Deep drilling
 - Small spacecraft missions
 - Cost-effective opportunities to continue compelling Mars science in parallel with Mars Sample Return
- Focused NASA technology investments will be essential to establish these capabilities

