# U.S. Offshore Wind – Getting Too Big, Too Fast – Where and How Innovation can Help

#### 2019 Marine Board Fall Meeting

Woods Hole, MA

06 November 2019



Center for Coastal Physical Oceanography

#### George Hagerman


Senior Project Scientist Old Dominion University CCPO 4111 Monarch Way, Suite 301 Norfolk, VA 23508

Email: <a href="mailto:hagerman@ccpo.odu.edu">hagerman@ccpo.odu.edu</a>

Phone: 757-683-5557



OF THE NATIONAL ACADEMIES



#### MARINE BOARD SPRING MEETING

April 27-28, 2011 Washington, D.C.

#### Selected Presentations

Oil Spills on Ice: Report on Industry Research Effort

A. Steen, Exxon/Mobil

P. Velez, Shell Int'l

Offshore Wind Energy Turbine Structural and Operating Safety

K. Michel, Herbert Eng.

### Background

(BOEMRE) is responsible for the orderly, safe, and environmentally responsible development of offshore renewables on the outer continental shelf.

BOEMRE requested that the NRC's Transportation Research Board's Marine Board conduct a study to guide the agency in the regulation and technical oversight of the nascent offshore wind energy industry in the United States.

### **Committee**

R. Keith Michel, Herbert Engineering Corporation, Alameda, California, Chair Bruce R. Ellingwood, Georgia Institute of Technology, Atlanta George M. Hagerman, Jr., Virginia Coastal Energy Research Consortium, Virginia Beach


Jan Behrendt Ibsoe, ABS Consulting, Inc., Houston, Texas
Lance Manuel, University of Texas at Austin
Walt Musial, National Renewable Energy Laboratory, Golden, Colorado
Robert E. Sheppard, Energo Engineering, Houston, Texas
Emil Simiu, National Institute of Standards and Technology, Gaithersburg,
Maryland

Susan W. Stewart, Pennsylvania State University, State College David J. Wisch, Chevron Energy Technology Company, Houston, Texas

Staff Madeline G. Woodruff, Study Director


### Scope of Study

- TASK 1: Standards and Practices
- The applicability and adequacy of existing standards and practices for the design, fabrication, and installation of offshore wind turbines.
- TASK 2: Role of Certified Verification Agents (CVAs)
  The expected role of the CVA in identifying standards to be used and conducting onsite inspections to verify compliance with the standards.
- TASK 3: CVA Qualifications
- The experience level, technical skills and capabilities, and support equipment and computer hardware/software needed to be considered a qualified CVA.



Policy Consequence	e:	Low	High
Scale of Impact		Small	Large
	Common	Routine Inspection, Maintenance & Repair No Policy Consequence  Lightning strike damaging rotor blade tip Small vessel collision damaging boat access landing	Fleetwide Component Failure Consequence: 1-2 year delay  • monopile/transition piece grout (serial design defect)  • gearbox bearings (serial manufacturing defect)
	Very Rare	Isolated Turbine Failure Low Policy Consequence (few months delay)  Blade strike collapsing turbine (waterspout during grid-outage) Ship collision collapsing turbine	Fleetwide Turbine Failure Consequence: 5-10 year delay  • Structural collapse in single first-of-a-kind project (Cape Wind)  • Structural collapse across multiple nth-of-a-kind projects
	ernal Event bability:		Mitigate by Standards and Certified Third-Party Reviews

# Marine Board 2011 Report led to AWEA Offshore Compliance Recommended Practice (OCRP) 2012



- AWEA OCRP 2012 is structured to mirror BOEM 30 CFR 585 "cradle to grave"
- Dozens of standards and guidelines from various industries and certifying bodies are cited and mapped to development process
- ➤ 50+ stakeholders/subject matter experts participated between 2009 and 2012
- AWEA OCRP published in October 2012 as a Recommended Practice



AWEA OCRP 2012 is a roadmap on how to use existing standards

#### **AWEA OCRP 2012 Codes and Standards Hierarchy**



AWEA OSW
Standards
Initiative is
replacing
OCRP 2012
with five new
Recommended
Practices

#### **Order of Document Priority**

Slide Credit: Rudy Hall – Keystone Engineering

### Offshore Wind 101: Energy Resource



### Wind Energy is a Derived Form of Solar Energy






Figure below shows nor'easter forming as cold dry air picks up heat and moisture from ocean




Winds move ~60% of excess equatorial solar energy towards the poles. Deep-ocean currents move the remaining ~40% (via thermo-haline circulation)

### At a Given Turbine Hub Height, Offshore Wind Speed is Greater than on Land




Effect of terrain roughness on wind-speed profiles. Values listed along curves are percentage of gradient wind speed. Because wind power density is proportional to wind speed cubed, wind power densities at a given turbine rotor hub height are much greater over open water.


### **US Offshore and On-Shore Wind Resource Classes**



### US Offshore Wind Resources are Near Coastal Metropolitan Load Centers



#### Northeast Business Case Stronger than Southeast




#### **Northeast Business Case Stronger than Southeast**




### **Offshore Wind 101: Economics**



#### Offshore Wind Levelized Cost of Energy Breakdown




#### Offshore Wind Levelized Cost of Energy Breakdown




Source: BVG Associates for Wind Europe


#### Offshore Wind Project CAPEX Trend




#### Offshore Wind Project CAPEX Trend




#### Offshore Wind <u>Turbine</u> CAPEX Trend




### Offshore Wind Turbine SIZE Trend Accelerating Rate of Growth since 2012



#### Offshore Wind Turbine SIZE Visualization



### Power Purchase Price of Offshore Wind Drops Dramatically for Projects in Service After 2019



- ▲ East Anglia One (UK)
- Hornsea 1 (UK)
- Borssele 1&2 (NL)
- Triton Knoll (UK)
- ×Hornsea 2 (UK)
- ■Borssele3&4 (NL)
- ◆ Gode Wind 4 (DE)

- □ Neart na Gaoithe (UK)
- Horns Rev 3 (DK)
- ▲ Vesterhav (DK)
- Kriegers Flak (DK)
- Moray Firth East (UK)
- ▲ Gode Wind 3 (DE)

Graph of European offshore wind power purchase prices for project in-service dates through 2024, based on recent auctions. Only UK projects (yellow) include transmission; NL, DE, and DK projects do not. Prices in 2017 USD; Source: https://files.vasierraclub.org/oswvision.pdf

Sources of US project contract prices:

#### Vineyard Wind (MA@2x400MW) -


www.windpoweroffshore.com/article/1489414/vine yard-wind-secures-levelised-cost-65-mwh

"The 20-year average cost of the two long-term contracts is \$84.23 per MWh in levelised nominal dollar terms. This is equivalent to a levelised net present value price in 2017 dollars of \$64.97 per MWh."

Revolution Wind (RI@400MW, CT@304MW) – www.windpoweroffshore.com/article/1525240/orst ed-sells-50-stakes-us-offshore-wind-sites

"Revolution Wind will generate electricity for a levelised cost of energy (LCOE) of \$73.68/MWh during its 20-year lifetime, Ørsted confirmed." www.ripuc.org/eventsactions/docket/4929-NGrid-ScheduleNG-5(REDACTED).pdf Indicates that LCOE is in 2018 dollars.

### Power Purchase Price of Offshore Wind Drops Dramatically for Projects in Service After 2019



- ▲ East Anglia One (UK)
- Hornsea 1 (UK)
- Borssele 1&2 (NL)
- Triton Knoll (UK)
- ×Hornsea 2 (UK)
- ■Borssele3&4 (NL)
- ◆ Gode Wind 4 (DE)

- □ Neart na Gaoithe (UK)
- Horns Rev 3 (DK)
- ▲ Vesterhav (DK)
- Kriegers Flak (DK)
- Moray Firth East (UK)
- ▲ Gode Wind 3 (DE)

Graph of European offshore wind power purchase prices for project in-service dates through 2024, based on recent auctions. Only UK projects (yellow) include transmission; NL, DE, and DK projects do not. Prices in 2017 USD; Source: https://files.vasierraclub.org/oswvision.pdf

Sources of US project contract prices:

#### Vineyard Wind (MA@2x400MW) -

www.windpoweroffshore.com/article/1489414/vine yard-wind-secures-levelised-cost-65-mwh

"The 20-year average cost of the two long-term contracts is \$84.23 per MWh in levelised nominal dollar terms. This is equivalent to a levelised net present value price in 2017 dollars of \$64.97 per MWh."


Revolution Wind (RI@400MW, CT@304MW) – www.windpoweroffshore.com/article/1525240/orst ed-sells-50-stakes-us-offshore-wind-sites

"Revolution Wind will generate electricity for a levelised cost of energy (LCOE) of \$73.68/MWh during its 20-year lifetime, Ørsted confirmed." www.ripuc.org/eventsactions/docket/4929-NGrid-ScheduleNG-5(REDACTED).pdf Indicates that LCOE is in 2018 dollars.


### **An East Coast Gold Rush**




# Mid-Atlantic Offshore Wind Lease Auctions and Acquisition Valuation of OCS Lands




### Bureau of Ocean Energy Management's East Coast Offshore Wind Lease Areas Total 1.74 Million Acres



### "During the gold rush it's a good time to be in the pick and shovel business" — Mark Twain



#### The Pick and Shovel Business of Offshore Wind




Expenditure profile for a typical offshore wind with the timing of investment decisions for key components

#### The Pick and Shovel Business of Offshore Wind



## 40% of VA+MD+DE+NJ Foundations as Jackets would have Steel Weight of 10 Nimitz-class CVNs



#### **Total Steel in 300 MW Offshore Wind Project**

PIN PILES + PRIMARY STEEL + SECONDARY STEEL

- = 800 metric tons per jacket x 60 jackets per project
- = 48,000 metric tons (47,240 long tons)

Foundation steel for a 300 MW offshore wind project has the same weight as all of the structural steel in a single Nimitz-class nuclear aircraft carrier (CVN)



#### Nimitz-class Nuclear Aircraft Carrier (CVN)


47,000 long tons of structural steel

Source: www.dailypress.com/news/dp-cvn77-01,0,5744629.htmlstory

### **Demonstrating Technology Innovation**



#### **Research Lease Status**



### **Major Research Funding Opportunity**

### National Offshore Wind Research and Development Consortium Notice of Upcoming Technical Challenges

First Research Pillar: Offshore Wind Plant Technology Assessment | Initial Release Version 1.0 | November 2018

The Consortium will competitively award ~\$32 million in research funding through open solicitations over the next four years

NYSERDA solicitation addresses the three research pillars of the US National Olishore Wind Strategy:

Pillar #1: Offshore Wind Plant Technology Advancement

Pillar #2: Offshore Wind Power Resource and Physical

Site Characterization

**Pillar #3**: Installation, Operations and Maintenance, and Supply Chain

First proposals target priority Challenge Areas identified for Pillar #1:


- (1) Array Performance and Control Optimization
- (2) Cost-Reducing Turbine Support Structures

### Research Pillar #1 – Challenge Area 1 (CA1) Array Performance and Control Optimization


Existing commercial lease project capacity pipeline within a day's sail from Hampton Roads depends on assumed turbine capacity density:

- Commercial leases off NJ, DE, MD, VA, and Kitty Hawk, NC have a total combined area of 3,056 square kilometers
- U.S. National Offshore Wind Strategy assumes a potential installed turbine density of 3 megawatts per square kilometer, or 3.0 MW/km², yielding a 9.17 GW pipeline
- Most recent European resource study (BVGA, June 2017) assumes 5.4 MW/km², yielding a 16.5 GW pipeline
- National Renewable Energy Laboratory studies show that when optimal turbine positioning is combined with wake steering by active yaw control, baseline of 5.4 MW/km² can be increased to 8.8 MW/km², yielding a 26.9 GW pipeline

Proving NREL optimization studies would grow the southern Mid-Atlantic project pipeline to the same levels as in Europe, where dramatic cost reductions were possible when pipeline >20 GW



#### National Renewable Energy Laboratory (NREL) Simulation of Wind Plant Layout & Control



**Source**: Katherine Dykes, National Renewable Energy Laboratory, 11 Oct 2017

### NREL Optimization for Hypothetical Project Yields 5% more Energy 70% more Energy per Unit Area


	Baseline	YawOpt	PosOpt	Combined
Mean power (MW)	78.86	84.91	78.86	78.84
Area (km²)	14.53	14.53	12.45	8.96
Power density (W/m <sup>2)</sup>	5.43	5.84	6.33	8.80
AEP(GWh)	1040.3	1094 (+5.2%)	1055.8 (+1.5%)	1095 (+5.3%)

122 GWh per km²



71.6 GWh

per km<sup>2</sup>




**Baseline**: fixed (original) turbine positions, turbines all yawed in mean wind direction

**YawOpt**: fixed (original) positions, turbines actively yawed for each wind direction

**PosOpt**: positions optimized, turbines all yawed in mean wind direction


**Combined**: positions optimized AND turbines actively yawed for each wind direction

#### **Combined Layout**



**Source**: Katherine Dykes, National Renewable Energy Laboratory, 11 Oct 2017 See <a href="http://onlinelibrary.wiley.com/doi/10.1002/we.1993/abstract">http://onlinelibrary.wiley.com/doi/10.1002/we.1993/abstract</a> for peer-reviewed paper.


### Virginia Research Leases Well-Positioned to Validate Wind Plant Layout & Control Modeling over Water




## Research Pillar #1 – Challenge Area 2 (CA2) Cost-Reducing Turbine Support Structures

A fixed platform is required to support a Doppler lidar or radar in RL2, to validate NREL computer simulations, and at the same time, this would demonstrate an innovative suction-bucket jacket foundation that can be fabricated and assembled in Hampton Roads for the entire East Coast market

- Demonstrate foundation installation without pile driving, which greatly expands offshore installation season from summer-only, daytime-only to **year-round**, **day-and-night**
- Validate jacket transparency to impact of breaking storm waves



First prototype suction-bucket jacket at Borkum Riffgrund I, pioneered by DONG Energy



Breaking wave at FINO-1 platform in 28 m water depth when significant wave height is only 6 m




Suction-bucket jacket for European Offshore Wind Deployment Center

# Doppler Lidar or Radar on Fixed Platforms in RL1 Aliquots also can Fully Map Resource


#### **Research Key Question 3**)

What innovative products and services can be demonstrated on Virginia's research leases to address wind-resource-related questions?


NASA Langley Research Center airborne Lidar measurements suggest large spatial variability in offshore wind resource across commercial lease area.




#### Doppler Lidar or Radar Suitability can be Tested at the Chesapeake Bay Entrance



#### Successful CA2 Proposal Lays Groundwork for Reference Metocean Station and Ocean Test Bed





	2017	2018			2019			2020					
	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
Cultural Hatal of DAD Agreed description	QT	<u> </u>	<u> </u>		Q-1	Q1	<u> </u>	23	QT	<u> </u>	<u> </u>	23	QT
Submittal of RAP Amendment													
BOEM Review/Approve RAP Amendment													
Design Engineering													
UXO Identification Survey													
Submittal of Facility Design Report													
Submittal of Fabrication and Installation Report													
BOEM Approval of FDR/FIR													
UXO Visual ROV Survey and Mitigation													
Offshore Component Fabrication								Jul-					
Onshore Construction								Aug 2019					
Offshore Construction													
COD ( Commercial Operation Date )													





# **Totally Autonomous Blade Inspection Enables Higher-Fidelity Structural Health Monitoring**



Piloted UAV inspection of land-based turbine (left) and offshore oil & gas platform (right)

#### BENEFITS OF UAV SYSTEM

- Autonomous quad-rotors charged by service power circuit, remotely actuated
- Can afford much more frequent scheduled and "as needed" inspections
- Earlier detection of damage enables timely repair rather than costly replacement
- Eliminates riskiest offshore operation for personnel



Visual inspection by rope technicians will provide commercial standard of service for blades and be used to benchmark UAV performance

**BP2** | Plan BP3 – BP5 activities; refine LCOE reduction estimates

Test components; validate visual & IR image interpretation

Integrate components and test on gantry at NASA-WFF

BP5

BP3

BP4

Install and operate a 3-quad system & charging garage on one turbine

#### **Next Time You Fly through Charlotte**

